

Specification Sheet



EncoreTM Vinyl Siding

General Description: EncoreTM siding provides the look of wood siding, but does not require the upkeep common to wood. Encore siding is available in a selection of profiles and finishes. It is appropriate for use in new construction for single family homes, multi-housing projects and light commercial developments. It is also ideal for remodeling.

Styles:

Profile	Finish	Panel Projection (Nominal)	Wall Thickness	Lock Design	Colors	Accessory Pocket
Triple 3" Clapboard	Woodgrain	1/2"	.040"	Post-formed	8	1/2", 5/8" or 3/4"
Double 4" Clapboard	Woodgrain	1/2"	.040"	Post-formed	16	1/2", 5/8" or 3/4"
Double 5" Clapboard	Woodgrain	1/2"	.040"	Post-formed	16	1/2", 5/8" or 3/4"
Double 4½" Dutchlap	Woodgrain	1/2"	.040"	Post-formed	16	1/2", 5/8" or 3/4"

Colors: Encore siding profiles are available in the industry's widest selection of colors. All colors are Spectrophotometer controlled and utilize exclusive PermaColorTM color science.

Buckskin*	Desert Tan	Natural Clay	Seagrass*
Castle Stone*	Heritage Cream	Oxford Blue	Snow*
Colonial White	Herringbone	Sandstone Beige*	Sterling Gray
Cypress*	Light Maple*	Savannah Wicker	Warm Sand*

*= not available in Triple 3" profile

STUDfinderTM: The patented STUDfinder Installation System combines precisely engineered nail slot locations with graphics. Nail slots are positioned 16" on center to allow for alignment with studs. STUDfinder graphics centered at each slot provide a quick and easy guide to help locate studs.

Accessories: CertainTeed manufactures a wide range of siding accessories that are compatible with Encore siding styles and colors. Accessory products include installation components, soffit, window and door trim, corner lineals, corner systems and decorative moldings.

Composition: Encore siding products are produced using CertaVinTM custom-formulated PVC resin. This resin is produced exclusively by CertainTeed, allowing CertainTeed to maintain the high quality of its siding products.

Technical Data: Encore siding is in compliance with ASTM specification for Rigid Polyvinyl Chloride (PVC) Siding D 3679, and the requirements of section R703.11 of the International Residential Code, and section 1405.14 of the International Building Code. Encore siding meets or exceeds the properties noted in Table 1.

Table 1

ASTM E 84	Meets Class A flame spread requirements as tested according to ASTM E84.
ASTM D 1929	Self-ignition temperature 813°F

Important Fire Safety Information: When rigid vinyl siding is exposed to significant heat or flame, the vinyl will soften, sag, melt or burn, and may thereby expose material underneath. Care must be exercised when selecting underlayment materials because many underlayment materials are made from organic materials that are combustible. You should ascertain the fire properties of underlayment materials prior to installation. All materials should be installed in accordance with local, state and federal Building Code and fire regulations.

Wind Load Testing: Encore Double 4" siding has been tested per ASTM D 5206 standard test method for resistance to negative wind load pressures of 58 psf, which equates to more than 212 mph (V_{ASD}) and 270 mph (V_{ULT}), when installed with nails, positioned 16" on center. Check with your local building inspector for wind load requirements in your area on the type of structure you are building.

Documents: CertainTeed Vinyl Siding meets the requirements of one or more of the following specifications.

Texas Department of Insurance Product Evaluation EC-11

Conforms to ASTM Specification D3679

Florida BCIS Approval FL1573

ICC-ES Evaluation Report ESR-1066

For specific product evaluation/approval information, call 800-233-8990.

Installation: Prior to commencing work, verify governing dimensions of building, examine, clean and repair, if necessary, any adjoining work on which the siding is in any way dependent for its proper installation. Sheathing materials must have an acceptable working surface. Siding, soffit and accessories shall be installed in accordance with the latest editions of CertainTeed installation manuals on siding and soffit. Installation manuals are available from CertainTeed and its distributors.

Warranty: CertainTeed supports Encore siding products with a Lifetime Limited Warranty including PermaColor Lifetime Fade Protection to the original homeowner. The warranty is transferable if the home is sold.

Technical Services: CertainTeed maintains an Architectural Services staff to assist building professionals with questions regarding CertainTeed siding products. Call 800-233-8990 for samples and answers to technical or installation questions.

Sample Short Form Specification: Siding as shown on drawings or specified herein shall be Encore Vinyl Siding as manufactured by CertainTeed Siding, Malvern, PA. The siding shall have a .040" nominal thickness. Installation shall be in accordance with manufacturer's instructions.

Three-part Format Specifications: Long form specifications in three-part format are available from CertainTeed by calling our Architectural Services Staff at 800-233-8990. These specifications are also available on our website at certainteed.com.



CertainTeed Corporation
20 Moores Road
Malvern, PA 19355
www.certainteed.com
© 01/18